

Contornare Porcelain Range


A refined stone-effect porcelain modelled on sedimentary stone, with subtle veining and fine fossil inclusions in five delicately shaded tones. The 20 mm outdoor tiles have a structured, slip-resistant surface and coordinate with matching indoor formats.

MATERIAL Coloured-body porcelain	APPLICATION Exterior	SLIP RATING R11 · PTV 36+ wet	FIRE RATING Class A1 _{fl}
-------------------------------------	-------------------------	----------------------------------	---------------------------------------

01 SIZES

1200 × 600 × 20 mm	RECTIFIED STRUCTURED	600 × 600 × 20 mm	RECTIFIED STRUCTURED
--------------------	-------------------------	-------------------	-------------------------

02 COLOURS



TIRAGGIO



DISEGNO



RIGA



FORMA



TRACCIARE

Colour samples are for guidance only. Natural variation in shade and texture is a feature of the product – please view a physical sample before ordering.

03 PACKING

Box & Pallet Data

SIZE	BOX			PALLET		
	TILES	M²	KG	BOXES	M²	KG
1200 × 600 × 20 mm	1	0.72	32.5	36	25.92	1170
600 × 600 × 20 mm	2	0.72	33.6	32	23.04	1075.2

04 PERFORMANCE

Technical Details

TECHNICAL FEATURE	TEST METHOD	REQUIRED VALUE	AVERAGE VALUE
Water absorption	ISO 10545-3	≤ 0.5%	◆ 0.05%
Breaking strength	ISO 10545-4	≥ 1300 N	◆ 13,600 N (20 mm)
Modulus of rupture	ISO 10545-4	≥ 35 N/mm²	◆ 50 N/mm²
Chemical resistance	ISO 10545-13	As indicated by manufacturer	◆ LA-HA resistant
Frost resistance	ISO 10545-12	No alteration	◆ Resistant
Slip resistance	DIN EN 16165 Annex B	-	◆ R11
Pendulum test (wet)	BS EN 16165 Annex C	-	◆ PTV 36+ wet (Sl. 96 – Sl. 55)
Shade variation	ANSI A137.1	As indicated by manufacturer	◆ V2 slight variation
Reaction to fire	EN 9239-1	UNI EN 13501-1	◆ Class A1 fl (floor)